

	P1250P3	P1375E3
380-415V,50Hz	1250,0 1000,0	1375,0 1100,0
220/127V, 60 Hz	-	-

0,8

- P1250P3  
( )  
1 12 10%

- P1375E3  
( )  
ISO

8528-3).

	Perkins 4012-46TWG2A	
	LL8224L	
- / :	12 / V	
: ( )	45,8 (2797,5)	
/ : ( )	160,0 (6,3)	
:	13.1:1	
:	T	
:	50	60
:	1500 /	-
: ( . )	1217,0 (1632,0)	-
: ( / )	2124,0 (308,0)	-
: / ( / )	9,5 (31,2)	-
( ) :	-	-
P1250P3 : ( / )	257,1 (67,9)	-
P1375E3 : ( / )	283,8 (75,0)	-
( / ) :	1001,0 (56926)	-
( / ) :	401,0 (22804)	-
( / ) :	89,0 (5061)	-
: ° (°F)	422 (792)	-
: 3/ ( / )	1116,0 (39411)	-
3/ ( / ) :	109,0 (3849)	-
3/ ( / ) :	180,0 (6357)	-

FG Wilson

( )	( )	( )	( )	( )
4820 (189,8)	1895 (74,6)	2424 (95,4)	9059 (19972)	9255 (20404)

ISO 8528, ISO 3046, IEC 60034, BS5000 NEMA MG-1/22.



www.FGWilson.com



P1250P3 / P1375E3



FG Wilson

FG Wilson ( )

FG Wilson

www.FGWilson.com

