

	P1350P1	P1500E1
380-415V,50Hz	1350,0 1080,0	1500,0 1200,0
220/127V, 60 Hz	-	-

0,8

- P1350P1  
( )  
1 12 10%

- P1500E1  
( )  
ISO

8528-3).

	Perkins 4012-46TWG3A	
	LL8224N	
- / :	12 / V	
: ( )	45,8 (2797,5)	
/ : ( )	160,0 (6,3)	
:	13.1:1	
:	T	
:	50	60
:	1500 /	-
: ( . )	1314,0 (1762,0)	-
: ( / )	2293,0 (332,6)	-
: / ( / )	9,5 (31,2)	-
( ) :	-	-
P1350P1 : ( / )	278,3 (73,5)	-
P1500E1 : ( / )	312,2 (82,5)	-
( / ) :	1128,0 (64148)	-
( / ) :	441,0 (25079)	-
( / ) :	96,0 (5459)	-
: ° (°F)	474 (885)	-
: 3/ ( / )	1620,0 (57210)	-
3/ ( / ) :	114,0 (4026)	-
3/ ( / ) :	182,0 (6427)	-

FG Wilson

( )	( )	( )	( )	( )
4888 (192,4)	1895 (74,6)	2469 (97,2)	9313 (20532)	9511 (20968)

ISO 8528, ISO 3046, IEC 60034, BS5000 NEMA MG-1/22.



www.FGWilson.com



P1350P1 / P1500E1



FG Wilson

FG Wilson ( )

FG Wilson

www.FGWilson.com

