

	P1500P3	P1650E3
380-415V, 50Hz	1500,0 1200,0	1650,0 1320,0
220/127V, 60 Hz	-	-

0,8

- P1500P3  
( )  
1 12 10%

- P1650E3  
( )  
( ) ISO

8528-3).

	Perkins 4012-46TAG2A	
	LL8224N	
- / :	12 / V	
: ( )	45,8 (2797,5)	
/ : ( )	160,0 (6,3)	
:	13.0:1	
:	T	
:	50	60
:	1500 /	-
: ( )	1437,0 (1927,0)	-
: ( / )	2508,0 (363,7)	-
: / ( / )	9,5 (31,2)	-
( ) :	-	-
P1500P3 : ( / )	296,6 (78,4)	-
P1650E3 : ( / )	326,3 (86,2)	-
( / ) :	1050,0 (59712)	-
( / ) :	485,0 (27581)	-
( / ) :	105,0 (5971)	-
: ° (°F)	450 (842)	-
: 3/ ( / )	1212,0 (42801)	-
3/ ( / ) :	128,0 (4520)	-
3/ ( / ) :	315,0 (11124)	-

FG Wilson

( )	( )	( )	( )	( )
5095 (200,6)	1900 (74,8)	2435 (95,9)	9720 (21429)	9910 (21848)

ISO 8528, ISO 3046, IEC 60034, BS5000 NEMA MG-1/22.



www.FGWilson.com



Aa

P1500P3 / P1650E3



FG Wilson

FG Wilson ( )

FG Wilson

www.FGWilson.com

